







4600

hand-drawn

for light and medium-weight curtains

Elegant, discrete track

4600



hand-drawn

for light and medium-weight curtains

elegant & discrete

The Qurails 4600 track is an attractive curved profile that can be mounted invisibly. The track flange is slightly longer on the visible side to conceal the fixing clamp. This minimises the unavoidable gap between the track and the ceiling. Simple ceiling mounting using a fixing clamp; no brackets are visible. A beautifully finished track that can be used in your home.

- The ideal track for sheers and lightweight or mediumheavy curtains.
- Easy to bend and exceptional quality.
- Can be forward or reverse bent in different radii.
- Concealed ceiling mounting.
- Compatible with the Qurails Flow System for regularly pleated curtains.
- Silent and smooth running, also round bends.



Standard colours



Features


Material: aluminium Colour: white Dimensions: 11×16 mm Weight profile: 137 gr/m Mounting: ceiling

Profile specifications

Aluminium profile:

Glider:





Colours with RAL code and lengths (m):

	RAL	4	5	6	7
white	9010			•	

Mounting surface:

- wood
- masonry/concrete

Bracket type:

• ceiling fixing clamp

Bending:

bending radius	bending tool		
R 10 cm	1012		
R 10 cm	1015		
R>80 cm	1018		
R 10 cm R > 80 cm			

Flow

The Qurails Flow System keeps pleats in curtains consistent. It can be used with small and wide channel tracks and, because of the broad assortment of components, it can be integrated in hand-drawn, cord-pulled and electrically operated systems.

The Flow System can also be used with curved curtain tracks. For further information, see the Flow product data sheet.

Specification guide Material


- Aluminium EN AW-6060-T66.
- Anodised in accordance with the Qualanod standard.
- Powder coated in accordance with the Qualicoat standard.

Mounting






Ceiling mounting with fixing clamp 2650 (including washer) with wood screws 2614.




Ceiling mounting with fixing clamp 2650 (including washer), before (a) and after tightening the clamp (b).

4600 without heading with glider 4010



Mounting guideline



The distance between the brackets can vary depending on the following factors: the mounting surface (wood, concrete or plaster), the weight of the curtains and the curtain fabric production method, the specific application and the system usage intensity. General advice: with the curtains open, place additional brackets where the pleats bunch together. Also place additional brackets before and after bends.

Standard parts

Curtain transport



4001 end stop white / grey / black



4010 glider white / grey / black

Mounting



2650 ceiling fixing clamp natural



2614 screw for 2650

Accessories



4653 end cap white



2652 connecting bridge natural

Optional parts

Curtain transport



2004 brake glider white / grey / black



4001-10-M-N end stop metal with eye natural



4002 end stop metal



4007 rotating glider white/silver/ grey/black



4010-50 glider white with hook 2023



4012 click-in glider white



4074-1000 carrier with overlap, a.o. for draw rod white / natural metallic / black



4075-1000 carrier without overlap, a.o. for draw rod white / natural metallic / black



2020 double hook white



2021 G-Hook white



2022 curtain hook white



2023 curtain hook white



2024-55 adjustable sew in hook white 55mm



2024-95 adjustable sew in hook white 95mm

Accessoires



1220 draw rod 100, 125, 150, 200 or 300 cm white / natural metallic / black / transparent

Technical specifications are subject to change without prior notice.

