







4701

hand-drawn

for light and medium-weight curtains

Compact and sleek

4701



hand-drawn

for light and medium-weight curtains

Compact and sleek

The Qurails 4701 track is a pretty rectangular profile. This curtain track is usually recessed into a wooden surface. An attractive, sleek track that can be used in your home or office building.

- The ideal track for sheers and lightweight or medium-heavy curtains.
- Easy to bend and exceptional quality.
- Can be forward or reverse bent in different radii.
- Concealed mounting on wood by screw or on concrete by ceiling bracket
- Compatible with the Qurails Flow System for regularly pleated curtains.
- Silent and smooth running, also round bends.



Standard colours





High quality, wear-resistant coating, highly colourfast, UV-resistant. Other RAL colours & special coatings on request.

Features

Material: aluminium

Colour: white, natural anodised


Afmetingen: 10 x 15 mm Weight profile: 137 gr/m¹ Mounting: ceiling

Profile/gliderspecifications

Aluminium profile:

Glider





Colours with RAL code and lengths (m):

4701 and 4701-PB PB with punch type 'B':

	RAL	4	5	6	7
white	9010			•	
natural				•	

Other punch types or colours on request.

Mounting surface:

- wood
- masonry/concrete

Bracket type:

• ceiling bracket

Bending:

bending radius	bending tool		
R 10 cm R 10 cm R>80 cm	1012 1015 1018		
R 10 cm R > 80 cm			

Flow

The Qurails Flow System keeps pleats in curtains consistent. It can be used with small and wide channel tracks and, because of the broad assortment of components, it can be integrated in hand-drawn, cord-pulled and electrically operated systems.


The Flow System can also be used with curved curtain tracks. For further information, see the Flow product data sheet.


Specification guide Material


- Aluminium EN AW-6060-T66.
- Anodised in accordance with the Qualanod standard.
- Powder coated in accordance with the Qualicoat standard.

Mounting


Pre-punched track from the 4700 series mounted using cross-head screws 2314







Mounting milled rail




Punch types



Additional mounting options


Standard punched hole type B. $(\emptyset 2.5 + 3 \times 10 \text{ mm slot, every } 15 \text{ cm})$ Other punch types are available on request.

Application example



Application of the 4753-12, a product with two functions: only as end cap or as end cap and end stop.

Mounting guideline (based on ceiling bracket)



The distance between the brackets can vary depending on the following factors: the mounting surface (wood, concrete or plaster), the weight of the curtains and the curtain fabric production method, the specific application and the system usage intensity. General advice: with the curtains open, place additional brackets where the pleats bunch together. Also place additional brackets before and after bends.

Standard parts

Curtain transport



4010 glider white / grey / black


Mounting



Dimming.

4750 ceiling bracket white/natural

2314



Accessories



4753-12 end cap white / grey

Optional parts

Curtain transport



2004 brake glider white / grey / black



4001-M end stop metal with eye natural



4002-M end stop metal



4003 spring stop plastic requires punch hole



4007 rotating glider white/ grey/silver/black



4007-LRS rotating glider LRS grijs / rotating glider LRS red



4010-50 glider white with hook 2023



4012 click-in glider white



4074-1000 carrier with overlap, a.o. for draw rod white / natural metallic / black



4075-1000 carrier without overlap, a.o. for draw rod white / natural metallic / black



2020 double hook white



2021 G-Hook white



2022 curtain hook white



2023 curtain hook white



2024-55 adjustable sew in hook white 55mm



2024-95 adjustable sew in hook white 95mm

Accessories



4048-08MM corner connection



4145 flexible dust cover



KVT-T1 draw rod 100, 125, 150, 200 of 300 cm white / natural metallic / black / transparent

Technical specifications are subject to change without prior notice.

